

J8T Tone Only POCSAG Pager



Features

Fully synthesized

Less stock needed on shelf, just program and go.

Vibrate only pager

The J8T is ideal for use as a vibrate only belt clip pager.

Great for getting attention

A simple light weight and inexpensive way for clients to contact their customers.

Single button operation

Button cancels received page.

Synchronize melody and vibrate

The vibration of the pager can be synchronized with the melody or bee being played.

Over the Air programming

The pager can be programmed over the air without needing to see the pager, making maintenance a breeze.

Supports various alerts

Can be set to ignore, beep, flash or vibrate when a page is received.

POCSAG Pager Specifications

Capcodes	4
Baud	512/1200/2400
Frequencies available	VHF (135 – 175MHz, 276 – 284 MHz), UHF (406 – 470MHz) 930 Mhz (928 – 932 MHz)
Frequencies	Synthesized, 2/2.5/3.25 khz
Decoding formats	Tone only
Channel spacing	20/25kHz or 10/12.5kHz
Frequency deviation	±4.5kHz
Modulation system	Carrier frequency shift keying (non return to zero)
Receiving sensitivity	512 bps 5 uV/m 1200 bps 7 uV/m 2400 bps 9 uV/m
Selectivity	65 db ±25kHz
Spurious rejection	More than 60db
Tone alert output	More than 75db(SPL) 30cm, frequency 2731Hz
Operating conditions	-20°C (-4°F) to +60°C (140°F) at 95% humidity
Weight	40g (1.41oz) including battery
Dimensions	40 x 62 x 18 mm (w/out clip) 1.57" x 2.44" x 0.71"
Battery	One "AAA" 1.5 volt



Pager Specifications

Alert type	Beep, flash and/or vibrate
Spring loaded belt clip	Yes
LED Low battery indicator	Yes
Sticker Recess	On the top of the pager for promotions
Vibrate & melody synchronization	Pager vibration can be synchronized to the alert beep
Single button operation	Pressing button cancels pager alert

Frequency Bands Available

VHF Band A	135-143MHz
VHF Band B	143-151MHz
VHF Band C	151-159MHz
VHF Band D	159-167MHz
VHF Band E	167-175MHz
VHF Band F	276-284MHz
UHF Band LA	406-414MHz
UHF Band LB	429-437MHz
UHF Band LC	439-446MHz
UHF Band L	446-454MHz
UHF Band M	454-462MHz
UHF Band H	462-470MHz
UHF Band S	929-932MHz

Pager Programming

Programming Software	DOS based
Over the air programmable (OTA)	Yes
Silent OTA programming	Yes
OTA pager off	Yes
OTA alert settings	Yes

Authorized Distributor:

For more information:

Hong Kong

K2Wireless HK Ltd
 Suite 1306, Lever Tech Centre,
 69-71 King Yip Street,
 Kwun Tong, Kowloon, Hong Kong.
 Phone: +85 222 174 108
 Direct Phone: +85 229 529 036
 Fax: +85 230 078 390

China

K2 Wireless
 809 Shenzhen High-Tech Building
 Nan-Shan, Shenzhen
 China PO-518057
 Phone: +86 755 2650 3891
 Fax: +86 755 2650 3894

sales@k2wireless.com.hk
www.k2wireless.com.hk